

NX-5155-G6 SPECIFICATION

MODEL	Nutanix : Per Node ([1] per Block) NX-5155-G6 (Configure to Order)
USE CASE(S)	Analytics and Big Data, Backup and Disaster Recovery, Files and Objects
SERVER COMPUTE**	Dual Intel Skylake: Silver 4108 [8 cores / 1.8 GHz]
STORAGE CAPACITY	
HYBRID (SSD-HDD)	[2, 4] x SSD: [960 GB, 1.92 TB, 3.84 TB or 7.68 TB], [8, 10] x HDD: [4 TB, 6 TB or 8 TB]
ALL FLASH (SSD-SED)	[4, 6, 8, 10, 12] x SSD: [960 GB or 1.92 TB]
HYBRID (SSD-HDD-SED)	[2, 4] x SSD: [960 GB or 1.92 TB], [8, 10] x HDD: [6 TB or 8 TB]
ALL FLASH (SSD)	[4, 6, 8, 10, 12] x SSD: [960 GB, 1.92 TB, 3.84 TB or 7.68 TB]
HYBRID (SSD-NVME)	[4, 6, 8] x SSD: [1.92 TB, 3.84 TB or 7.68 TB]
MEMORY	128 GB, 192 GB
NETWORK CONNECTIONS	
SERVERBOARD	[2] x 10 GBase-T ports (Port 1 is IPMI failover) (or) [1] x 10/100/1000 GBASE-T (IPMI port)
PCIE SLOT 1, 2, 3	[1] x Dual-port 10 GbE SFP+ NIC (or) [1] x Quad-port 10 GbE SFP+ NIC (or) [1] x Dual-port 10 GBASE-T NIC (or) [1] x Dual-port 25 GbE SFP28 NIC (or) [1] x Dual-port 40 GbE QSFP28 NIC
GPU	N/A
CERTIFICATIONS	Energy Star, CSAus, FCC, CSA, ICES, CE, KCC, RCM, VCCI-A, BSMI, EAC, SABS, INMETRO, S-MARK, UKRSEPRO, BIS
DIMENSIONS (PER BLOCK)	Height: 3.50"(89 mm) Width: 17.20"(437 mm) Depth: 28.46"(723 mm) Rack Units: 2U 1N
WEIGHT (PER BLOCK)	Standalone: 72.09 lbs.(32.7 kg) Package: 66.45 lbs.(30.14 kg)
SYSTEM COOLING	4x 80mm heavy duty fans with PWM fan speed controls
OPERATING	Op Temp Rng: 50° to 95°F(10° to 35°C)

MODEL

Nutanix : Per Node ([1] per Block) NX-5155-G6 (Configure to Order)

**ENVIRONMENT
(PER BLOCK)**Non-Op Temp Rng: -40° to 158°F(-40° to 70°C)
Op Humidity Rng (non-condensing): 20% to 95%
Non-Op Humidity Rng: 5% to 95%**POWER
CONSUMPTION**Maximum: 806W
Typical: 550W**POWER SUPPLY
(DUAL SUPPLY /
BLOCK)**1.6kW Output @100-240V, 13.0-8.0A, 50-60Hz;
80PLUS TITANIUM**THERMAL
DISSIPATION**Maximum: 2750 BTU/hr
Typical: 1860 BTU/hr**OPERATING
REQUIREMENTS
(PER BLOCK)**

Input Voltage: 100-240V AC auto-range, Input Frequency: 50-60Hz

**** number of cores per CPU socket.**