

NX-8155-G6 SPECIFICATION

MODEL	Nutanix : Per Node ([1] per Block) NX-8155-G6 (Configure to Order)
USE CASE(S)	Database and Business Critical Apps
SERVER COMPUTE**	Dual Intel Skylake: Silver 4108 [8 cores / 1.8 GHz] Gold 6148 [20 cores / 2.4 GHz] Gold 5120 [14 cores / 2.2 GHz] Gold 6154 [18 cores / 3.0 GHz] Gold 6152 [22 cores / 2.1 GHz] Platinum 8180 [28 cores / 2.5 GHz] Silver 4114 [10 cores / 2.2 GHz] Gold 6128 [6 cores / 3.4 GHz]
STORAGE CAPACITY	
HYBRID (SSD-HDD)	[2, 4] x SSD: [960 GB, 1.92 TB or 3.84 TB], [8, 10] x HDD: [4 TB, 6 TB or 8 TB]
ALL FLASH (SSD-SED)	[4, 6, 8, 10, 12] x SSD: [960 GB or 1.92 TB]
HYBRID (SSD-HDD-SED)	[2, 4] x SSD: [960 GB or 1.92 TB], [8, 10] x HDD: [6 TB or 8 TB]
ALL FLASH (SSD)	[4, 6, 8, 10, 12] x SSD: [960 GB, 1.92 TB, 3.84 TB or 7.68 TB]
HYBRID (SSD-NVME)	[4, 6, 8] x SSD: [1.92 TB or 3.84 TB]
MEMORY	192 GB, 256 GB, 384 GB, 512 GB, 768 GB, 1024 GB, 1536 GB
NETWORK CONNECTIONS	
SERVERBOARD	[2] x 10 GBase-T ports (Port 1 is IPMI failover) (or) [1] x 10/100/1000 GBASE-T (IPMI port)
PCIE SLOT 1, 2, 3	[1] x Dual-port 10 GbE SFP+ NIC (or) [1] x Quad-port 10 GbE SFP+ NIC (or) [1] x Dual-port 10 GBASE-T NIC (or) [1] x Dual-port 25 GbE SFP28 NIC (or) [1] x Dual-port 40 GbE QSFP28 NIC
GPU	N/A
CERTIFICATIONS	Energy Star, CSAus, FCC, CSA, ICES, CE, KCC, RCM, VCCI-A, BSMI, EAC, SABS, INMETRO, S-MARK, UKRSEPRO, BIS
DIMENSIONS (PER BLOCK)	Height: 3.50"(89 mm) Width: 17.20"(437 mm) Depth: 28.46"(723 mm) Rack Units: 2U 1N
WEIGHT	Standalone: 72.09 lbs.(32.7 kg)

MODEL Nutanix : Per Node ([1] per Block) NX-8155-G6 (Configure to Order)

(PER BLOCK)	Package: 66.45 lbs.(30.14 kg)
SYSTEM COOLING	4x 80mm heavy duty fans with PWM fan speed controls
OPERATING ENVIRONMENT (PER BLOCK)	Op Temp Rng: 50° to 95°F(10° to 35°C) Non-Op Temp Rng: -40° to 158°F(-40° to 70°C) Op Humidity Rng (non-condensing): 20% to 95% Non-Op Humidity Rng: 5% to 95%
POWER CONSUMPTION	Maximum: 1070W Typical: 700W
POWER SUPPLY (DUAL SUPPLY / BLOCK)	1.6kW Output @100-240V, 13.0-8.0A, 50-60Hz; 80PLUS TITANIUM
THERMAL DISSIPATION	Maximum: 3650 BTU/hr Typical: 2388 BTU/hr
OPERATING REQUIREMENTS (PER BLOCK)	Input Voltage: 100-240V AC auto-range, Input Frequency: 50-60Hz

** number of cores per CPU socket.